

OXYGEN GENERATOR

MINI MODEL

ARNIKA
—COMPANY—

TRYCOMP[®]
Heavy Duty



Advanced System in Gas Separation
Oxygen Production Unit





MINI MODEL OXYGEN GENERATORS TECHNICAL DATA

Model	Weight (Kg)	Dimensions L x D x H (mm)	Content (μm)	Inlet Air Pressure (Barg)	O ₂ Output Pressure (Barg)	Power V/ph/Hz
OKSİPAK 5	100	250x850x1120	0.01	4	3	110 - 230 / 1 / 50 - 60
OKSİPAK 10	160	300x850x1620	0.01	4	3	110 - 230 / 1 / 50 - 60
OKSİPAK 15	200	400x955x1270	0.01	4	3	110 - 230 / 1 / 50 - 60
OKSİPAK 20S	240	400x955x1670	0.01	4	3	110 - 230 / 1 / 50 - 60
OKSİPAK 20M	280	400x955x1930	0.01	4	3	110 - 230 / 1 / 50 - 60
OKSİPAK 20L	300	400x955x2000	0.01	4	3	110 - 230 / 1 / 50 - 60

MINIMUM OXYGEN OUTPUT FLOW WITH COMPRESSED AIR INLET PRESSURE OF 4 BAR (g)

Pin = 4 (BARG)	O ₂ Flow (Nm ³ /h)	Compr. Air Consumption (Nm ³ /h)
MODEL / PURITY	95 %	95 %
OKSİPAK 5	1,065	13,845
OKSİPAK 10	2,13	27,69
OKSİPAK 15	3,195	41,535
OKSİPAK 20S	4,26	55,38
OKSİPAK 20M	5,325	69,225
OKSİPAK 20L	6,39	83,07

OUR COMPANY MAY CHANGE THE VALUES IN THE CATALOGUE ACCORDING TO THE RESEARCH AND DEVELOPMENT STUDIES. FOR BIGGER CAPACITIES AND MODELS, PLEASE CONTACT WITH OUR TEAM



MINI MODEL OXYGEN GENERATORS TECHNICAL DATA

Model	Weight (Kg)	Dimensions L x D x H (mm)	Content (μm)	Inlet Air Pressure (Barg)	O ₂ Output Pressure (Barg)	Power V/ph/Hz
OKSİPAK 5	100	250x850x1120	0.01	6,5	5,5	110 - 230 / 1 / 50 - 60
OKSİPAK 10	160	300x850x1620	0.01	6,5	5,5	110 - 230 / 1 / 50 - 60
OKSİPAK 15	200	400x955x1270	0.01	6,5	5,5	110 - 230 / 1 / 50 - 60
OKSİPAK 20S	240	400x955x1670	0.01	6,5	5,5	110 - 230 / 1 / 50 - 60
OKSİPAK 20M	280	400x955x1930	0.01	6,5	5,5	110 - 230 / 1 / 50 - 60
OKSİPAK 20L	300	400x955x2000	0.01	6,5	5,5	110 - 230 / 1 / 50 - 60

MINIMUM OXYGEN OUTPUT FLOW WITH COMPRESSED AIR INLET PRESSURE OF 6,5 BAR (g)

Pin = 6,5 (BARg)	O ₂ Flow (Nm ³ /sa) 5,5 (BARg)	Compr. Air Consumption (Nm ³ /h)	O ₂ Flow (Nm ³ /sa) 5,5 (BARg)	Compr. Air Consumption (Nm ³ /h)	O ₂ Flow (Nm ³ /sa) 5,5 (BARg)	Compr. Air Consumption (Nm ³ /h)
MODEL / SAFLIK	90 %	90 %	93 %	93 %	95 %	95 %
OKSİPAK 5	0,35	3,55	0,3	3,55	0,25	3,55
OKSİPAK 10	0,8	7,9	0,65	7,9	0,56	7,9
OKSİPAK 15	1,2	12	1	12	0,85	12
OKSİPAK 20S	1,97	19,7	1,6	19,7	1,4	19,7
OKSİPAK 20M	2,8	28,6	2,2	28,6	2	28,6
OKSİPAK 20L	3,2	32	2,6	32	2,2	32

FİRMAMIZ KATALOGDAKİ DEĞERLERİ ARAŞTIRMA, GELİŞTİRME ÇALIŞMALARINA GÖRE PARALEL OLARAK DEĞİŞTİREBİLİR. DAHA BÜYÜK KAPASİTELER VE MODELLER İÇİN LÜTFEN EKİBİMİZLE İLETİŞİME GEÇİNİZ.